

General Purpose, Three Phase Globetrotter® NEMA Premium® Efficiency Dripproof

Features:

- ⊕ Meets or exceeds NEMA Premium® efficiencies
NEMA Premium® models are in compliance with EISA2007
- 182T-215T models steel frame, 254T-449T models cast iron frame
- Inverter Duty 10:1 Variable Torque and 2:1 Constant Torque, 1.0 SF
- 1.15 Service Factor
- Class F Insulation
- Standard assembly F1, reversible to F2 assembly
- UL Recognized, CSA Certified, CE Mark
- Three year warranty



Rigid Base

HP	RPM	VOLTS	FRAME	CAT. NO.	MODEL NO.	STOCK	LIST PRICE	MULT. SYMB.	NOM. EFF.	F.L. AMPS	WEIGHT	"C" DIM.	FOOT NOTES	C FACE KIT
1 1/2	1200	230/460	182T	GT0005	182TTDB6076	✓	\$623	E1	86.5	4.8-4.4/2.2	75	13.72		A160
2	1200	208-230/460	184T	GT0008	184TTDB6076	✓	\$634	E1	87.5	6.4-5.8/2.9	99	14.72		A160
3	1800	208-230/460	182T	GT0010	182TTDB6026	✓	\$551	E1	89.5	8.4-7.8/3.9	76	13.72		A160
	1200	208-230/460	213T	GT0011	213TTDB6076	✓	\$870	E1	88.5	9.2-8.8/4.4	156	17.52		A161
5	3600	208-230/460	182T	GT0012	182TTDB6001	✓	\$581	E1	86.5	13.2-11.8/5.9	126	13.72		A160
	1800	208-230/460	184T	GT0013	184TTDB6026	✓	\$620	E1	89.5	13.6-12.4/6.2	86	14.72		A160
	1200	208-230/460	215T	GT0014	215TTDB6076	✓	\$1,012	E1	89.5	15.2-14.0/7.0	281	17.52		A161
7 1/2	3600	208-230/460	184T	GT0015	184TTDB6001	✓	\$714	E1	88.5	19.0-17.0/8.5	143	14.72	A	A160
	1800	208-230/460	213T	GT0016	213TTDB6026	✓	\$802	E1	91.0	20.7-19.0/9.5	160	17.52		A161
	1200	208-230/460	254T	GT0017	254TTDCA6076	✓	\$1,266	E1	90.2	22.0-21.0/10.5	281	22.64		A163
10	3600	208-230/460	213T	GT0018	213TTDB6001	✓	\$916	E1	89.5	25.5-23.0/11.5	150	17.52		A161
	1800	208-230/460	215T	GT0019	215TTDB6026	✓	\$947	E1	91.7	26.9-25.0/12.5	220	17.52		A161
	1200	208-230/460	256T	GT0020	256TTDCA6076	✓	\$1,578	E1	91.7	29.6-27.6/13.8	305	24.22		A163
15	3600	208-230/460	215T	GT0021	215TTDB6001	✓	\$1,342	E1	90.2	38.0-34.0/17.0	184	17.52		A161
	1800	208-230/460	254T	GT0022	254TTDCA6026	✓	\$1,311	E1	93.0	40.0-38.0/19.0	310	22.64		A163
	1200	208-230/460	284T	GT0023	284TTDCA6076	✓	\$2,078	E1	91.7	42.5-40.0/20.0	414	25.71	YD	A165
20	3600	208-230/460	254T	GT0024	254TTDCA6001	✓	\$1,546	E1	91.0	51.0-46.0/23.0	300	22.64	YD	A162
	1800	208-230/460	256T	GT0025	256TTDCA6026	✓	\$1,623	E1	93.0	53.0-49.0/24.5	360	24.22	YD	A163
	1200	208-230/460	286T	GT0026	286TTDCA6076	✓	\$2,532	E1	92.4	58.0-54.0/27.0	457	27.09	YD	A165
25	3600	208-230/460	256T	GT0027	256TTDCA6001	✓	\$1,969	E1	91.7	64.0-57.0/28.5	315	24.22	YD	A162
	1800	208-230/460	284T	GT0028	284TTDCA6026	✓	\$1,915	E1	93.6	66.0-62.0/31.0	424	25.71	YD	A165
	1200	208-230/460	324T	GT0029	324TTDCA6076	✓	\$3,016	E1	93.0	72.0-68.0/34.0	695	28.55	YD	A167
30	3600	208-230/460	284TS	GT0030	284TSTDCA6001	✓	\$2,435	E1	91.7	76.0-68.0/34.0	396	24.41	YD	A164
	1800	208-230/460	286T	GT0031	286TTDCA6026	✓	\$2,210	E1	94.1	81.0-74.0/37.0	483	27.09	YD	A165
	1200	208-230/460	326T	GT0032	326TTDCA6076	✓	\$3,535	E1	93.6	83.5-78.5/39.0	760	29.73	YD	A167
40	3600	208-230/460	286TS	GT0033	286TSTDCA6001	✓	\$2,931	E1	92.4	100-90.0/45.0	452	25.79	YD	A164
	1800	208-230/460	324T	GT0034	324TTDCA6026	✓	\$2,777	E1	94.5	105-95.0/47.5	581	28.55	YD	A167
	1200	208-230/460	364T	GT0035	364TTDCB6086	✓	\$4,537	E1	94.1	106-99.0/49.5	875	31.69	YD	A169
50	3600	208-230/460	324TS	GT0036	324TSTDCA6001	✓	\$3,573	E1	93.0	124-93.0/46.5	548	27.05	YD	A166
	1800	208-230/460	326T	GT0037	326TTDCA6026	✓	\$3,310	E1	94.5	131-118/59.0	710	29.73	YD	A167
	1200	208-230/460	365T	GT0038	365TTDCB6086	✓	\$5,223	E1	94.1	132-122/61.0	930	33.27	YD	A169
60	3600	208-230/460	326TS	GT0039	326TSTDCA6001	✓	\$4,275	E1	93.6	148-134/67.0	590	28.23	YD	A166
	1800	208-230/460	364T	GT0040	364TTDCB6060	✓	\$3,935	E1	95.0	153-139/69.5	1005	31.69	YD	A169
	1200	230/460	404T	GT0041	404TTDCB6086	✓	\$6,286	E1	94.5	144/72.0	975	37.20	YD	A415

Catalog numbers (Cat No.) highlighted in bold blue have efficiency levels that meet EISA requirements

Blue shaded areas are Cast Iron Frames

Continued on next page.