

Close Coupled Pump Motors



For specific requirements of centrifugal pumps where the pump impeller is mounted directly on the motor shaft.

Horsepower: 1 – 60 HP

Phase: Single and Three Phase

RPM: 1800 and 3600 RPM

Voltage:

- 115/230
- 230
- 575
- 208-230/460
- 200
- 230/460 Volts

Efficiency: Standard, Energy and Premium Efficient


Enclosure:

- Open Dripproof (ODP)
- Totally Enclosed, Fan Cooled (TEFC)
- Hazardous Location

Mounting: Footed and Footless

Shaft Types:

- JM
- JP
- Westcoast



Close Coupled Pump ODP Motor



Close Coupled Pump TEFC Motor



U.S. MOTORS® brand Close Coupled Pump Motors are designed to meet a variety of applications

Single Phase:

- Open Dripproof (ODP)
 - JM Shaft Footed
 - JP Shaft Footed
- Totally Enclosed, Fan Cooled (TEFC)
 - JM Shaft Footed
 - JP Shaft Footed

Three Phase:

- Open Dripproof Standard and Premium Efficient
 - JM Shaft Footed & Footless
 - JP Shaft Footed & Footless
 - Westcoast Shaft Footed (Standard Efficient only)
- Open Dripproof Energy Efficient
 - JM Shaft Footed
 - JP Shaft Footed
- Hazardous Location, Dual Label
 - JM Shaft Footed
- Totally Enclosed, Fan Cooled (TEFC) Standard and Energy Efficient
 - JM Shaft Footed
 - JP Shaft Footed
 - Westcoast Footed (Standard Efficient Only)
- Totally Enclosed, Fan Cooled (TEFC) Premium Efficient
 - JM Shaft Footed

† All marks shown within this document are properties of their respective owners.